

8MM BELT AND PULLEY COMBINATIONS

BB CHEVY STANDARD DECK

1440 BELT 115-94 TOOTH COUNT
INTERCOOLED W/ 1600 BELT 102-86 TOOTH COUNT

BB CHEVY TALL DECK

1440 BELT 108-86 TOOTH COUNT
INTERCOOLED W/ 1600 BELT 97-86 TOOTH COUNT

SB CHEVY

1440 BELT 115-94 TOOTH COUNT
INTERCOOLED W/ 1600 BELT 102-86 TOOTH COUNT

16 RIB BELT AND PULLEY COMBINATIONS

BB CHEVY STANDARD DECK

1455 BELT 11.8" - 10.6" COMBINED DIAMETER
INTERCOOLED W/ 1650 BELT 11.6" - 10.3" COMBINED DIAMETER

BB CHEVY TALL DECK

1495 BELT 11.8" - 10.9" COMBINED DIAMETER
INTERCOOLED W/ 1650 BELT 10.6" - 10.1" COMBINED DIAMETER
INTERCOOLED W/ 1700 BELT 11.8" - 11.1" COMBINED DIAMETER

192 SB CHEVY WITH 6.4" BOTTOM PULLEY

1195 BELT 2.85" THRU 3.35" TOP PULLEY
1225 BELT 3.60" THRU 4.35" TOP PULLEY

250 BB CHEVY STD DECK WITH 6.4" BOTTOM PULLEY

1320 BELT 2.85" THRU 3.35" TOP PULLEY
1345 BELT 3.60" THRU 4.35" TOP PULLEY

250 BB CHEVY TALL DECK WITH 6.4" BOTTOM PULLEY

1345 BELT 2.85" THRU 3.35" TOP PULLEY
1365 BELT 3.60" THRU 4.35" TOP PULLEY

THE COMBINED TOOTH COUNTS OR DIAMETERS OF THE TOP AND BOTTOM PULLEYS MUST STAY WITHIN THE MAX AND MIN TOOTH COUNTS OR DIAMETERS FOR EACH SPECIFIC ENGINE COMBINATION